

EASYDET SMART 30

RF DUAL PEDESTALS

Reliable and proven RF (Radio-Frequency) two-pedestal system with good detection of tags and adhesive labels. The Easydet system is suitable for most environments and has excellent resistance to challenging environments and other article surveillance systems.

The RF Easydet system is ideal for retailers located in shopping centers, who are looking for a standard loss prevention system that provides good, reliable protection. The high-quality acrylic pedestal is designed to meet the stylish and modern requirements of premium retailers while still maintaining the cost-effectiveness of the Easydet system.

Features & options:

- Metal detection
- Alarm light
- Decoration light
- Low frequency option





For retailers facing losses due to professional shoplifters equipped with foil-lined bags, the SMART pedestal line can be upgraded with our integrated analog MetalSpy (aluminum foil bag detector), enhancing the level of your merchandise protection



The **premium crystal acrylic** panel is manufactured from the highest grade, preventing discoloration and warping. The included multi-colored LED lights can be configured to not only display the alarm colour that you wish, but also to light the antenna permanently in an attractive glow.

Design comparison

PEDESTAL COMPARISON	EASYDET SMART 30	NG DUAL CRYSTAL 40
FEATURES / OPTIONS		
INTEGRATED METAL DETECTION ³	○	○
INTEGRATED VISITOR COUNTING ^{3,5}	✘	○
SMART DIRECTIONAL ALARMS ³	✘	○
REMOTE MAINTENANCE AND DIAGNOSTICS ⁵	✘	○
WIRELESS COMMUNICATION	✘	○
RGB ALARM LIGHT	✓	✓
POWER SAVING MODE	✘	✓
COLOUR OPTIONS	S / B / W	S / B / W
DIMENSIONS		
HEIGHT	151.5	165.5 cm
WIDTH	29.4 cm	36.5 cm
DEPTH	2.0 cm	2.0 cm
BASE DIMENSIONS (H×W×D)	31.4 × 29.9 × 10.2 cm	23.3 × 35.5 × 9.6 cm
WEIGHT	13.0 kg	15.8 kg
DETECTION RANGE		
DETECTION RANGE SOFT LABELS ¹	DUAL up to 145 cm	DUAL up to 165 cm
DETECTION RANGE HARD TAG ²	DUAL up to 160 cm	DUAL up to 185 cm
PRODUCT CODES		
	RECEIVER / TRANSMITTER	
SILVER COLOUR		
	RS-ERCSS / RS-ETCSS	

Legend: ✓ included ✘ not available ○ optional.

¹tested with AMERSEC 40x40 mm soft labels in all orientations ²tested with original AMERSEC Picco50 tags in all orientations ³minimum of 2 pedestals required ⁴visitor counting sensors required ⁵e-COMM communication module required with a Storemonitor account ⁶MMS Controller unit required

System specification

Operating frequency – 3.25–8.2 MHz
Sweep frequency – 164 Hz
Power – 24 V DC
Consumption – 25 W

