

MONO CLASSIC 30, MONO CLASSIC 30X, MONO CLASSIC OPEN 30, MONO CLASSIC 30 ADVERT

RF MONO PEDESTALS

Reliable and proven RF (Radio-Frequency) transceiver system with good detection of tags and adhesive labels. The HF Mono system is suitable for supermarkets and hypermarkets, where the pedestal can be placed to cover two checkout exits.

The HF Mono system excels in large stores where it can be linked together in large numbers, while providing good and reliable protection at an attractive cost. The aluminum pedestal frame is designed to provide a cost-effective solution while still maintaining a stylish and modern look.

For those who prefer the proven classic we offer CLASSIC 30 and CLASSIC 30X fully covered with plastic or glass panels.

CLASSIC 30 ADVERT offers a space for advertising, while CLASSIC 30 OPEN is an open frame with the protected top part of the desk for a more secure and durable functioning.

Features & options:

- Variable design
- Low frequency option





Our Classic line of pedestals are available in three standard colours (silver, black and white) as well as two stylish options. The standard Classic pedestal is a lightweight, fully closed pedestal with opaque panels in one of our standard colour. The second option is transparent design with acrylic panels added to protect crossbars from possible damage at high traffic places.



An **advertisement** panel on your security system can be an additional sales tool with our “easy slide” access to printed banner replacement. An identical pedestal but without the opaque panel, the Classic X pedestal features a transparent acrylic surface that blends in with the surrounding space. The Open pedestal is an empty frame without a plastic panel.

Design comparison

PEDESTAL COMPARISON	MONO CLASSIC 30	MONO CLASSIC 30X	MONO CLASSIC OPEN 30	MONO CLASSIC 30 ADVERT
FEATURES / OPTIONS				
ADVERTISEMENT PANEL	✗	✗	✗	✓
TRANSPARENT DESIGN	✗	✓	✓	✗
INTEGRATED METAL DETECTION ³	✗	✗	✗	✗
INTEGRATED VISITOR COUNTING ^{3,5}	✗	✗	✗	✗
SMART DIRECTIONAL ALARMS ³	✗	✗	✗	✗
REMOTE MAINTENANCE AND DIAGNOSTICS ⁵	✗	✗	✗	✗
WIRELESS COMMUNICATION	✗	✗	✗	✗
RGB ALARM LIGHT	✗	✗	✗	✗
POWER SAVING MODE	✗	✗	✗	✗
COLOUR OPTIONS	S / B / W	S / B / W	S / B / W	S / B / W
DIMENSIONS				
HEIGHT	152.5 cm	152.5 cm	152.5 cm	152.5 cm
WIDTH	29.4 cm	29.4 cm	29.4 cm	29.4 cm
DEPTH	5.2 cm	5.2 cm	5.2 cm	5.2 cm
ADVERTISEMENT	✗	✗	✗	24.3 x 123.5 cm
WEIGHT	5.8 kg	6.4 kg	5.3 kg	6.75 kg
DETECTION RANGE				
DETECTION RANGE SOFT LABELS ¹	MONO	MONO	MONO	MONO
	up to 75 cm each side	up to 75 cm each side	up to 75 cm each side	up to 75 cm each side
DETECTION RANGE HARD TAG ²	MONO	MONO	MONO	MONO
	up to 110 cm each side	up to 110 cm each side	up to 110 cm each side	up to 110 cm each side
PRODUCT CODES				
SILVER COLOUR	RS-H30CLS	RS-H30CLXS	RS-H30CLOS	RS-H30CLS-AD

Legend: ✓ included ✗ not available ○ optional.

¹tested with AMERSEC 40x40 mm soft labels in all orientations ²tested with original AMERSEC Picco50 tags in all orientations ³minimum of 2 pedestals required ⁴visitor counting sensors required ⁵e-COMM communication module required with a Storemonitor account ⁶MMS Controller unit required

System specification

Operating frequency – 1.81–8.2 MHz
Power – 15 V AC–18 V AC
Consumption – 10 W

